FIBERGLASS **EXTENSION LADDER**



SERIES FE4200HD

375 LBS

(Includes weight of user plus materials)

A TRIED AND TRUE CLASSIC.

When you have a good one, you keep it. Heavy duty and versatile, this time tested ladder series proves to be a workplace necessity. Equipped with aluminum swivel safety shoes, rope & pulley system, and rung plate connectors, this ladder is built to last. An extended array of compatible accessories give you the ability to mix and create the perfect tool for your specific onsite demands.

 $\mathbf{M} \mathbf{A} \mathbf{X} \mathbf{L} \mathbf{O} \mathbf{C} \mathbf{K}^{\mathsf{m}}$



TOUGHEST


STRONGEST LIGHTEST RUNGLOCK 44

FE4200HD-301



Swivel Shoe

Aluminum swivel shoe with full metal boot.



Rope and Pulley

Heavy duty pulley and thick rope system



Plate Connection

Aluminum rung plate connector plates



BECAUSE WORK AIN'T PLAY.









Round End Caps

Heavy duty non-marring end caps. FE4200HD-E62



Combination Spur and Shoe

Rotate spur down for extra security on penetrable surfaces. FE4200HD-E63



Combination Pole Grip & Cable Hook

The Combination Pole Grip & Cable Hook adds versatility for midspan jobs or utility pole work. FE4200HD-E03

* Round End Caps, Combination Spur & Shoe, and Combination Pole Grip & Cable Hook can be ordered together. add suffix -301



Front-Mounted Pulley

Allows for the ladder to be completely extended with greater ease and efficiency. rubber tread is made for

FE4200HD-E55



Web Pole Grip

This strong, flexible nylon webbing with corrugated use against utility poles.

FE4200HD-E05

3 1/4"

3 11/16"




Rigid Pole Grip

The steel-plated V-shape bar is covered with heavy rubber tread for extra biting grip.

BASE

15 3/8"



DUTY RATING	MODEL	TOTAL LENGTH	LENGTH EACH SECTION	MAX. EXTENDED LENGTH	MAX. REACH	MAX. STANDING HEIGHT	APPROX. WEIGHT (LB)	APPROX. VOLUME (FT3)
IAA	FE4216HD	16'	8′	13′	15′11″	9′4″	41	7.2
IAA	FE4220HD	20'	10′	17′	19′ 10″	13′3″	50	8.9
IAA	FE4224HD	24'	12′	21′	23′8″	17′1″	58	10.6
IAA	FE4228HD	28'	14′	25′	27′7″	21′	67	12.3
IAA	FE4232HD	32'	16′	29′	31′5″	24′ 10″	81	14

6"

6 1/16"



MODEL

16'-28'

32′



