CROSSXSTEP | >>>



TYPE IAA

375LBS I NAN CAPACITY (Includes weight of user plus materials)

2 IN 1 LADDER USE LADDER AS A LEANING AND **STEP** LADDER



WORK **USER** to any area



TOP No more OSHA fines due to missing duty rating labels. Heat Transfer Top keeps duty rating displayed in sight for the user.

FEATURING LOUISVILLE LADDER'S TECHNOLOGY







FIBERGLASS STEPLADDER

THE GREATEST


We invented the Cross Step to change the way you work. And we created our exclusive LeanGreen technology to make it clear that your worksite is compliant. Because when it comes to innovative elevation, there's only one pioneer that's **INNOVATION** helping you get the job done. That designs, develops, and drives the advancements that others can only IN ELEVATION dream of. That casts the mold, that sets the standard. There's only one that's Built to be Above.



CROSSXSTEP | >>>









2 Locking Latch to secure rear section.





Inside Spreader Brace

Heavy-duty interior support braces protect the ladder during transport to extend its lifespan.



④ Raptor Boot and SHOX[™]

Slip-resistant boot protects fiberglass. SHOX™ provide superior impact absorption.



FXS1400HD FLYER JUNE 2022 © Louisville Ladder, Inc. All rights reserved.

						SHELF LADDER		STEPLADDER	
MODEL	LADDER SIZE	BOTTOM WIDTH (IN)	APPROX. SPREAD (IN)	APPROX. WEIGHT (LBS)	APPROX. CUBES (FT)	HIGHEST STANDING LEVEL (IN)	MAX. REACH	HIGHEST STANDING LEVEL (IN)	MAX. REACH
FXS1404HD	4'	20 1⁄4	24	16	4.0	11"	7'6"	1'11"	8'6"
FXS1406HD	6'	23 ¼	36	23	6.8	2'10"	9'5"	3'9"	10'4"
FXS1408HD	8'	26 1⁄4	48	31	10.1	4'9"	11'4"	5'8"	12'3"
FXS1410HD	10'	29 ¼	60	39	14.0	6'8"	13'3"	7'7"	14'2"
FXS1412HD	12'	32 ¾	71	48	18.5	8'6"	15'1"	9'6"	16'1"

