


COMBINATION LADDER

TYPE IAA
375 lbs
 LOAD CAPACITY
includes weight of user plus materials


HEAVY DUTY
 BOOT
 NON-MARRING
 TREAD



FRONT SECTION
 HAS 3" FLAT
 STEP WITH
 SLIP-RESISTANT
 TREAD



PRO END CAP
 NON-MARRING
 HEAVY DUTY
 PROTECTS SURFACE
 FROM DAMAGE



WEB POLE GRIP



INNER BRACES



* REAR SECTION WITH ROUND RUNGS

MODEL	LADDER SIZE	MAX. EXTENDED LENGTH	MAX. STANDING LEVEL		MAX. REACH		FLARED SECTION			
			STEPLADDER	EXTENSION	STEPLADDER	EXTENSION	MIN. OUTSIDE DIMENSION	MAX. OUTSIDE DIMENSION	WEIGHT (LBS)	APPROX. CUBES
FXC1206	6'	9' 8"	3' 9"	5' 7"	10' 4"	12' 2"	17%	24%	34	7
FXC1207	7'	11' 8"	4' 8"	7' 6"	11' 3"	14' 1"	17%	25%	39	8.3
FXC1208	8'	13' 8"	5' 7"	9' 5"	12' 2"	16'	17%	26%	43	9.6

*OUTSIDE DIMENSION (ALL): 14%



1-800-666-2811

www.LOUISVILLELADDER.com

