

CROSS PINNACLE



SERIES FCP1400HD

FIBERGLASS PLATFORM TO LEANING LADDER


TYPE IAA

375 LBS

LOAD CAPACITY
(Includes weight of user plus materials)

2 IN 1 PLATFORM LADDER

USE LADDER AS A **PLATFORM**
AND **LEANING LADDER**



**LARGE
SLIP RESISTANT
PLATFORM WITH
BUILT IN
OVERFLOW SLOTS**

WORK FACING MULTIPLE DIRECTIONS

It is not recommended that worker face ladder steps while on platform

COMPATIBLE WITH PINNACLE GATE ACCESSORY

Installing the Pinnacle Gate accessory allows 4 sided contact, permitting 360° of working access.



LOUISVILLE
LADDER

BECAUSE WORK AIN'T PLAY.

ANSI
Meets or exceeds requirements
of American National Standard Institute
ANSI A14.5





1 ProTop™

The V-shaped Pro Top™ leans on walls, poles, and onto and into corners. The integrated bumper protects the working surface while the top provides multiple tool slots and tool tether anchor attachment points.



2 Larger Platform

Overflow slots keep materials from building up on the surface. Slip-resistant tread on this spacious platform allows for secure work and comfortable movement.



3 Extended Handrail

36" heavy-duty handrail runs from platform to peak providing a secure 3-sided barrier.

*Works with Pinnacle Gate Accessory to allow for 360° work access.



4 Raptor Boot™

Polypropylene copolymer upper boot and thick, non-marring thermoplastic elastomer tread deliver maximum protection for your ladder and its cargo.



5 SHOX™

Advanced impact absorption system offers superior protection against damage.



FCP1400HD FLYER JUNE 2022 © Louisville Ladder, Inc. All rights reserved.

MODEL	PLATFORM HEIGHT	BOTTOM WIDTH (IN)	APPROX. SPREAD (IN)	APPROX. WEIGHT (LBS)	APPROX. CUBES (FT)	HIGHEST STANDING LEVEL (IN)	MAX. REACH
FCP1402HD	1' 11"	21 15/16	30 1/4	25	8.8	1' 11"	8' 6"
FCP1403HD	2' 10"	23 15/16	35 1/2	30	11.4	2' 10"	9' 5"
FCP1404HD	3' 10"	25 7/16	41 1/4	34	14.1	3' 10"	10' 5"
FCP1406HD	5' 8"	28 3/8	54	43	20.1	5' 8"	12' 3"
FCP1408HD	7' 7"	31 5/8	66	52	27.2	7' 7"	14' 2"



WWW.LOUISVILLELADDER.COM

